

# Lock Out

**DESCRIPTION:** SafeChoice Lock Out is designed to perform two functions: first, to help seal in the outgassing of chemicals found in carpet fibers, and second to help repel dirt and stains.

SafeChoice Lock Out sealer is designed to be used in conjunction with **SafeChoice Carpet Shampoo** (to clean) and **SafeChoice Carpet Seal** (to seal carpet backing). This three-part system cleans out and helps to seal in the irritating chemicals found throughout a typical carpet.

**USE ON:** SafeChoice Lock Out is generally suitable for synthetic carpets and rugs. Because of variations in materials and production processes used by different manufacturers, you should always spot test to insure compatibility with your carpet. Wool fibers generally do not react well to water based products, so SafeChoice Lock Out is not recommended for wool.

**PRODUCT NUMBER AND CONTAINER SIZE:**  
61230 (quart) and 61130 (gallon).

**ADVANTAGES / SIGNIFICANT BENEFITS:**

- Fights indoor air pollution by stopping the outgassing of irritating materials from carpet fibers - the only product in the world so designed.
- Especially important for professional maintenance people who maintain centrally-ventilated buildings where occupants are subject to the effects of all toxic discharges within the building, including those from carpet and building and maintenance products.
- Odorless - pleasant for user and occupant.
- Repels dirt and stains.
- Safely used by and for the chemically sensitive.

**APPLICATION:** Carpet should be vacuumed and cleaned using **SafeChoice Carpet Shampoo** to remove, as much as possible, the petrochemical residue from the fibers. After cleaning, seal carpet with **SafeChoice Carpet Seal**, then allow the carpet to dry thoroughly before proceeding with application of SafeChoice Lock Out. For old carpeting follow the same procedure of vacuuming and cleaning with **SafeChoice Carpet Shampoo**. For carpets exceeding four years in age use of **SafeChoice Carpet Seal** may be optional. Carpet must be completely dry whether or not **SafeChoice Carpet Seal** is required. Using a hand-held pump sprayer (similar to a garden sprayer), spray a fine mist of SafeChoice Lock Out evenly and uniformly over the entire carpet surface. Do not oversaturate. Allow the carpet to dry to touch before permitting floor traffic.

**COVERAGE:** One gallon of SafeChoice Lock Out covers approximately 300 square feet for medium to tight weave carpet.

**CLEAN-UP:** Clean tools and equipment with water while they are still wet.

**DRYING/CURING TIME:** Two to four hours in moderate heat and humidity. Cool temperatures and/or high humidity may increase drying time.

**LIMITATIONS:** Not recommended for wool or velour carpet. Surface must be completely dry before application. Surface should be dry to touch before permitting floor traffic.

**HEALTH PRECAUTIONS:** As with all cleaning products, keep container tightly closed and out of the reach of children. Do not ingest. If swallowed, drink two (2) glasses of water to dilute. In case of eye contact, flush immediately with plenty of water for 15 minutes. *If you are chemically sensitive, always test for personal tolerance.*

**LIMITED LIABILITY:** SafeChoice® products are guaranteed not to be defective when properly applied. Liability express or implied is limited to replacement of product or refund of purchase price and does not include liability for labor costs or consequential damages. Variable factors out of manufacturer's control, such as environmental conditions, application techniques, and surface conditions are critical to results obtained. Users are expected to exercise reasonable care to determine suitability of the product for each application. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of AFM products. **Always test in small, inconspicuous areas before application to the entire surface.**